

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 4 of 19

- 1 1. (Currently Amended) A ~~handheld~~mobile device comprising:
2 a first segment;
3 a second segment moveably coupled to the first segment to move primarily along one axis
4 between a contracted position and an extended position, wherein an overall length of
5 the mobile device is reduced when the second segment is moved towards the
6 contracted position as compared to when the second segment is in the extended
7 position ;
8 a display assembly provided by the first segment;
9 a first input mechanism provided by the second segment;
10 wherein the first input mechanism overlays a portion of the display assembly when the
11 second segment is in the contracted position, and wherein the first input mechanism is
12 positioned away from the display assembly so that the portion of the display assembly
13 is accessible to contact by a user when the second segment is in the extended position.
- 1 2. (Currently Amended) The ~~handheld computer~~mobile device of claim 1,
2 wherein the display assembly includes a first section having a cross-section
3 comprising a digitizer pad and a screen, and a second section comprising the
4 digitizer pad without the screen, and wherein the portion of the display
5 assembly that is overlaid by the first input mechanism includes the second
6 section.
- 1 3. (Currently Amended) The ~~handheld computer~~mobile device of claim 1,
2 wherein the display assembly includes ~~an immediate~~a character recognition

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 5 of 19

3 section configured to immediately recognize and display assembly a character
4 entry, and wherein the portion of the display assembly that is overlaid by the
5 first input mechanism includes the immediate character recognition section.

1 4. (Currently Amended) The ~~handheld computer~~mobile device of claim 1,
2 wherein an exterior surface of the second segment includes a front panel,
3 wherein a plurality of input mechanisms including that include the first input
4 mechanism being are actuatable by from the front panel, and wherein the front
5 panel overlays the portion of the display assembly when the second segment is
6 in the contracted position.

1 5. (Currently Amended) The ~~handheld computer~~mobile device of claim 1,
2 wherein the first input mechanism includes a multi-directional member.

1 6. (Currently Amended) The ~~handheld computer~~mobile device of claim 1,
2 further comprising a plurality of input mechanisms including that include the
3 first input mechanism, and wherein at least one of the plurality of input
4 mechanisms is a button that can be pressed to cause an input to be entered onto
5 the ~~handheld computer~~mobile device.

1 7. (Currently Amended) The ~~handheld computer~~mobile device of claim 1,
2 further comprising a plurality of input mechanisms including that the first input
3 mechanism, and wherein at least one of the plurality of input mechanisms is
4 actuatable by detecting surface contact.

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 6 of 19

1 | 8. (Currently Amended) The ~~handheld-computer~~mobile device of claim 1,
2 | wherein the first segment includes a first rail, the first rail being positioned on a
3 | lateral side of the first segment, and wherein the second segment includes a first
4 | connecting member that is engaged to the first rail, the first connecting member
5 | slideable along a length of the first rail to enable the second segment to move
6 | between the contracted position and the extended position.

1 | 9. (Currently Amended) The ~~handheld-computer~~mobile device of claim 1,
2 | wherein the first segment includes a first rail and a second rail, and wherein the
3 | second segment includes a first connecting member and a second connecting
4 | member, wherein the first connecting member ~~being~~is engaged to the first rail,
5 | the second connecting member being engaged to the second rail, the first
6 | connecting member and the second connecting member each being slideable
7 | along a length of the respective first rail and second rail to enable the second
8 | segment to move between the contracted position and the extended position.

1 | 10. (Currently Amended) The ~~handheld-computer~~mobile device of claim 9,
2 | wherein the first segment comprises a front shell, a midframe, and a bottom
3 | shell, and wherein the first rail is formed onto a first surface of the midframe,
4 | and wherein the second rail is formed onto a second surface of the midframe.

1 | 11. (Currently Amended) The ~~handheld-computer~~mobile device of claim 9,
2 | wherein the first rail and the second rail extend lengthwise on a back surface of
3 | the first segment.

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 7 of 19

1 12. (Currently Amended) The ~~handheld computer~~mobile device of claim 11,
2 wherein the second segment includes a back plate that slides adjacent to the
3 back surface of the ~~handheld computer~~mobile device.

1 13. (Currently Amended) The ~~handheld computer~~mobile device of claim 11,
2 wherein the back plate of the second segment includes the first connecting
3 member that slides within the first rail, and the second connecting member that
4 slides within the second rail.

1 14. (Currently Amended) The ~~handheld computer~~mobile device of claim 1,
2 wherein the first segment is slideably coupled to the second segment so that the
3 second segment moves ~~in along~~ a single ~~direction axis~~ when moving between
4 the contracted position and the extended position.

1 15. (Currently Amended) The ~~handheld computer~~mobile device of claim 1,
2 further comprising a midframe coupled to the first segment and the second
3 segment.

1 16. (Currently Amended) The ~~handheld computer~~mobile device of claim 15,
2 wherein the second segment connects to the midframe to move between the
3 contracted position and the extended position.

1 17. (Currently Amended) The ~~handheld computer~~mobile device of claim 16,
2 wherein the midframe includes a first rail, and wherein the second segment
3 includes a first connecting member that is engaged to the first rail, the first

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 8 of 19

4 connecting member moving a distance in the first rail to enable the second
5 segment to move between the contracted position and the extended position.

1 18. (Currently Amended) The ~~handheld computer~~mobile device of claim 16,
2 wherein the midframe includes a first rail and a second rail, and wherein the
3 second segment includes a first connecting member and a second connecting
4 member, the first connecting member being engaged to the first rail, the second
5 connecting member being engaged to the second rail, the first connecting
6 member and the second connecting member each moving a distance in the
7 respective first rail and second rail to enable the second segment to move
8 between the contracted position and the extended position.

1 19. (Currently Amended) A ~~handheld computer~~mobile device comprising:
2 a first segment;
3 a ~~contact sensitive~~ display assembly accessible on a front surface of the first
4 segment; and
5 a second segment slideably coupled to the first segment to move between a
6 contracted position and an extended position, the second segment being
7 positioned to overlay and reduce an area of the contact-sensitive display
8 assembly that is accessible to contact when moved from the extended
9 position to the contracted position;
10 wherein an overall length of the mobile device is reduced when the second
11 segment is moved towards the contracted position as compared to when
12 the second segment is in the extended position.

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 9 of 19

1 | 20. (Currently Amended) The ~~handheld computer~~mobile device of claim 19,
2 | wherein the display assembly is contact-sensitive.

1 | 21. (Currently Amended) The ~~handheld computer~~mobile device of claim 20,
2 | wherein all of the display assembly is accessible to receive contact as input
3 | when the second segment is in the extended position.

1 | 22. (Currently Amended) The ~~handheld computer~~mobile device of claim 20,
2 | wherein the display assembly includes an immediate character recognition
3 | section configured to immediately recognize and display a character entry, and
4 | wherein a portion of the display assembly that is overlaid by the first segment
5 | includes the immediate character recognition section.

1 | 23. (Currently Amended) The ~~handheld computer~~mobile device of claim 20,
2 | wherein the display assembly includes a first section having a cross-section
3 | comprising a digitizer pad and a screen, and a second section comprising the
4 | digitizer pad without the screen, and wherein a portion of the display assembly
5 | that is overlaid by the first housing segment includes the second section.

1 | 24. (Currently Amended) The ~~handheld computer~~mobile device of claim 19,
2 | further comprising a midframe coupled to the first segment and the second
3 | segment.

1 | 25. (Currently Amended) The ~~handheld computer~~mobile device of claim 24,
2 | wherein the midframe includes a first rail, and wherein the second segment

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 10 of 19

3 includes a first connecting member that is engaged to the first rail, the first
4 connecting member moving a distance in the first rail to enable the second
5 segment to move between the contracted position and the extended position.

1 26. (Currently Amended) The ~~handheld computer~~mobile device of claim 24,
2 wherein the midframe includes a first rail and a second rail, and wherein the
3 second segment includes a first connecting member and a second connecting
4 member, the first connecting member being engaged to the first rail, the second
5 connecting member being engaged to the second rail, the first connecting
6 member and the second connecting member each moving a distance in the
7 respective first rail and second rail to enable the second segment to move
8 between the contracted position and the extended position.

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 11 of 19

- 1 | 27. A housing assembly for a ~~handheld computer~~ mobile device, the housing
2 | comprising:
3 | a first housing segment having a front surface, the front surface including an opening to
4 | provide access to a display surface for the ~~handheld computer~~ mobile device;
5 | a second housing segment moveably coupled to the first housing segment to move between a
6 | contracted position and an extended position, the second housing segment overlaying
7 | a first region of the opening of the first housing segment when in the contracted
8 | position, the first region of the opening that is overlaid by the second housing
9 | segment being reduced as the second housing segment is moved from the contracted
10 | position towards the extended position; and
11 | wherein an overall length of the housing assembly is reduced when the second housing
12 | segment is moved from the extended position towards the contracted position.
- 1 | 28. (Original) The housing assembly of claim 27, wherein none of the first area is
2 | overlaid by the second housing segment when the second housing segment is in the extended
3 | position.

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 12 of 19

1 29. (Currently Amended) The housing assembly of claim 27, wherein,
2 the first housing segment provides a top housing for the ~~handheld computer~~mobile device,
3 the top housing having a reduced section provided towards a bottom of the top
4 housing,
5 the second housing segment provides a bottom housing for the ~~handheld computer~~mobile
6 device,
7 the bottom housing being configured to overlay at least a majority of the reduced section of
8 the top housing when in the contracted position, and
9 wherein the bottom housing ~~being is~~ configured to at least not overlay the majority of the
10 reduced section when in the extended position.

1 30. (Original) The housing assembly of claim 29, wherein the second housing segment
2 includes a back plate that extends from the bottom housing to slide along a back surface of
3 the first housing segment when the second housing segment is moved between the contracted
4 position and the extended position.

1 31. (Original) The housing assembly of claim 27, wherein the first housing segment
2 comprises a top shell, a midframe, and a bottom shell.

1 32. (Original) The housing assembly of claim 31, wherein the midframe has a first rail on
2 a first lateral side of the midframe, and a second rail on a second lateral side of the midframe.

1 33. (Original) The housing assembly of claim 31, wherein the second housing segment
2 includes a bottom housing and a back plate, the bottom housing being shaped to abut a top
3 housing of the first housing segment when the second housing segment is moved into the

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 13 of 19

4 contracted position, the back plate being positioned to slide along a back surface of the first
5 housing segment when the second housing segment is moved between the contracted position
6 and the extended position.

1 34. (Currently Amended) The housing assembly of claim 33, wherein an interior surface
2 of the second housing segment includes a first connecting member and a second connecting
3 member, the first connecting member and the second connecting member being slideably
4 engaged with the first rail and the second rail.

1 35. (Original) The housing assembly of claim 32, wherein a back surface of the first
2 housing segment includes a first rail and a second rail, the back surface opposing the front
3 surface.

1 36. (Original) The housing assembly of claim 35, wherein the second housing segment
2 includes a bottom housing and a back plate, the bottom housing being shaped to abut a top
3 housing of the first housing segment when the second housing segment is moved into the
4 contracted position, the back plate being positioned to slide along a back surface of the first
5 housing segment when the second housing segment is moved between the contracted position
6 and the extended position.

1 37. (Original) The housing assembly of claim 36, wherein the back plate is dimensioned
2 to slide between the first rail and the second rail on the back surface of the first housing
3 segment, and wherein the back plate includes a first connecting member to engage the first
4 rail, and a second connecting member to engage the second rail.

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 14 of 19

38. (Original) The housing assembly of claim 27, wherein the first housing segment includes a top shell, a midframe, and a bottom shell, a first rail formed on a first lateral side of the midframe, a second rail formed on a second lateral side of the midframe, and wherein a back surface of the first housing segment includes a third rail and a fourth rail.

39. (Currently Amended) The housing assembly of claim 38, wherein the second housing segment includes a first bottom housing and a back plate, and wherein the first housing segment includes a top housing and a reduced section, the bottom housing of the second housing segment being moveable over the reduced section of the first housing segment to abut the top housing when the second housing segment is positioned in the contracted position, wherein the back plate is dimensioned to move within the ~~third~~first rail and the ~~fourth~~second rail of the first housing segment to slide along the back surface of the first housing segment, and wherein an interior of the bottom housing includes a first connecting member that is engaged with the first rail provided on the midframe, and a second connecting member that is engaged with the second rail provided on the midframe, ~~the bottom housing.~~

40. (Original) The housing assembly of claim 37, wherein the first connecting member and the second connecting member are each biased, wherein the first rail is configured to retain the first connecting member in an unbiased state at a position corresponding to the contracted position and at another position corresponding to the extended position, and wherein the second rail is configured to retain the second connecting member in an unbiased state at a position corresponding to the contracted position and at another position corresponding to the extended position.

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 15 of 19

41. (Currently Amended) A ~~handheld computer~~mobile device comprising:
a first segment providing a first input feature;
a second segment slideably coupled to the first segment to move move primarily along one axis between a contracted position and an extended position, the second segment providing a second input feature, wherein the second segment overlays a portion of the first segment when moved towards the contracted position so as to reduce a length of the ~~handheld computer~~mobile device.
42. (Currently Amended) The ~~handheld computer~~mobile device of claim 41, wherein the first input feature corresponds to a contact-sensitive display.
43. (Currently Amended) The ~~handheld computer~~mobile device of claim 41, wherein the second input feature corresponds to one or more buttons.
44. (Currently Amended) The ~~handheld computer~~mobile device of claim 41, wherein the first segment has a reduced section that has a lesser thickness than a remainder of the first portion, and wherein the second segment slides over the reduced section when moving towards the contracted position.
45. (New) A mobile device comprising:
a first segment;
a second segment moveably coupled to the first segment to move primarily along one axis between a contracted position and an extended position, wherein an overall length of the mobile device is reduced when the second segment is moved towards the

Response to Office Action Dated March 18, 2004
U.S. Patent Application No. 09/932,213
Page 16 of 19

contracted position as compared to when the second segment is in the extended position ;

a display assembly provided by the first segment;

a first input mechanism provided by the second segment;

wherein when the second segment is in the contracted position, the first segment and the second segment are at least partially overlaid, so that access to at least one of either the first input mechanism and the display assembly is at least partially blocked.

46. (New) The mobile device of claim 45, wherein the display assembly is contact-sensitive.

47. (New) The mobile device of claim 45, wherein the first input mechanism includes a set of one or more buttons.

48. (New) The mobile device of claim 45, wherein the first input mechanism includes a plurality of one or more mechanical input mechanisms.

49. (New) The mobile device of claim 45, wherein the first segment overlays the second segment so that the display assembly covers at least a portion of the first input mechanism.

50. (New) The mobile device of claim 45, wherein the second segment is configured to slide towards and away from the first segment.